

ALL THE BENEFITS OF BEVMAX4. ALL THE VERSATILITY OF A NARROW UNIT.

NARROW
BEVMAX
MODEL 3800-4



47" WIDE UNIT

39" NARROW UNIT

✓ SAME FOOTPRINT AS A STANDARD STACK UNIT

✓ INCREASED SALES VS. STACK UNITS

✓ EASIER TO HANDLE AND TRANSPORT

✓ SUPERIOR ENERGY SAVINGS EXCEEDS BOTH ENERGY STAR TIER 2 AND DEPARTMENT OF ENERGY 2012 STANDARDS

✓ ONE PLATFORM - TWO SIZES - COMMON PARTS

✓ MEETS ADA AND ANSI REQUIREMENTS

NARROW
BEVMAX
MODEL 3800-4



CRANE®

DixieNarco
Vending System

NARROW BEVMAX4 MODEL 3800-4



ENERGY EFFICIENT REFRIGERATION PLATFORM

...two times more energy efficient than machines made five years ago.

	kWh per year	Increased Operating Costs per Year	
BevMAX4 - Narrow	1376		
Competitor A	2042	\$73.45	+48%
Competitor B	2100	\$79.85	+53%
5-Year Old Machine	2871	\$164.89	+108%

Tier 2



BevMax4 Narrow exceeds ENERGY STAR Tier 2 Standards. The only Glass Front to exceed the Department of Energy 2012 Conservation Standards.

Figures based on the national average per kWh - January 2009 (\$0.1103 per kWh). *Actual energy usage may vary based on environmental conditions.

Only BevMax4 has been designed to enhance the consumer experience and meet the operational needs of bottlers and vending operators.



RELIABILITY

The most reliable, dependable vending solution proven by independent 20,000 vend operating tests; 80,000 vend life-cycle tests and comprehensive field testing exceeding 238,000 vends.

VERSATILITY

Increase your sales and profitability by replacing an aging stack vender with a Narrow BevMax4. With a similar footprint as many stack machines, the BevMax4 offers an alternative size for those accounts with space restrictions.

EFFICIENCY


A "shimless" vend mechanism addresses costly labor and service concerns. Load any package in any position. Eliminate loading errors. Load fast with both hands. Bottles remain firmly in place (even if the machine is rocked).

SPEED

Who likes to wait in line? BevMax4 delivers product in only 8 seconds. Faster delivery time increases sales, speed of service and customer satisfaction.

SIMPLIFIED MAINTENANCE

Low profile modular refrigeration platform removes from the front or the back of the machine.



SPECIFICATIONS

- DIMENSIONS**
72" H x 39" W x 32" D
(183cm H x 99cm W x 82cm D)
- WEIGHT**
545 lbs. empty (247 kg)
- ELECTRICAL**
120 VAC, 60 Hz, 10.2 amps
MDB Level 3 Controller
- REFRIGERATION**
134A CFC-Free Refrigerant Gas
1/3 HP Compressor
- CERTIFICATIONS**
UL, CUL, CE, FCC, NOM, CTICK



3330 DIXIE-NARCO BLVD., WILLISTON, SC 29853
TEL: 800-688-9090 | FAX: 803-266-5150 | WWW.DIXIENARCO.COM

AQUAFINA IS A REGISTERED TRADEMARK OF PEPSICO, INC