



High Value Visibility Vendor (HV3)

FEATURES & SPECIFICATIONS

V21 Model Number	521 HV3	621 HV3	721 HV3	821 HV3
Total Can Capacity	196	544	680	800
Total PET Bottle Capacity	91	240	300	360
# of Selections / Columns	6 / 7	6 / 8	10 / 10	10 / 10
Dimensions* - H x W x D	61" x 29" x 24"	72" x 32.5" x 35"	72" x 39.5" x 35"	79" x 39.5" x 35"
Shipping Weight*	365 lbs.	570 lbs.	660 lbs.	725 lbs.
Operation Voltage	115v 60Hz	115v 60Hz	115v 60Hz	115v 60Hz
Amp Rating	4	8	8	8
Energy Consumption (DOE)	≤ 3.2 kWh/day	≤ 3.0 kWh/day	≤ 3.1 kWh/day	≤ 3.5 kWh/day
Lighting	LED	LED	LED	LED
Refrigerant	R-134a	R-134a or CO2 (optional)	R-134a or CO2 (optional)	R-134a or CO2 (optional)
Lock Type	T-Handle or E-Lock (optional)	T-Handle or E-Lock (optional)	T-Handle or E-Lock (optional)	T-Handle or E-Lock (optional)
Capacity per Column				
12oz. Can	28	68	68	80
20oz. PET Bottle**	13	30	30	36

* Dimensions and shipping weight will vary slightly.

** Product capacities will vary based on the shape and size of the bottle.



- The HV3 is a low cost, energy efficient alternative to the Pepsi HVV. Standard Features include: LED lights, curved signface, sleek new selection buttons and DBV panel, T-Handle lock assembly, UL certified, ADA compliant, ENERGY STAR qualified & meets or exceeds DOE & EPA requirements.
- Rugged top retainer ensures consistent product alignment every time the door is closed.
- The V21 stack allows for maximum flexibility during product loading. Most products can be loaded caps to back, butt-to-butt, or in combination.
- The V21 has a full function MDB controller with DEX/UCS, recycler and wireless telemetry compatibility.
- Energy management features included on every model make the V21 one of the most energy efficient machines available: real time clock, lighting and refrigeration controls, cyclopentane injected foam insulation (HFC free) and now the option of **alternative natural refrigerant**.
- The V21 utilizes 24 volt, DC motors that are installed with only two screws for easy servicing. There are no micro switches or timing cams.
- Slide out loading rack allows for greater access to the columns for 2 handed product loading.
- The time tested V21 product delivery system design ensures reliable vending due to reduced sensitivity to package diameter and shape.

SandenVendo America, Inc. offers a complete line of parts, accessories, supplies and add-on security devices - call or visit www.vendoco.com for more information.

PEPSI, PEPSI-COLA, and the PEPSI BIG BOLD BLUE design are registered trademarks of PepsiCo, Inc.



SandenVendo America, Inc.
 10710 Sanden Drive, Dallas, TX 75238
 P: 214-765-9066 F: 214-340-8029
 P: 1-800-344-7216 F: 1-800-541-5684
www.vendoco.com



Copyright © 2015 SVA
 Part # 1148988-04

REV F 4/15



High Visibility Vendor (HVV)

FEATURES & SPECIFICATIONS

V21 Model Number	621 HVV	721 HVV	821 HVV
Total Can Capacity	544	680	800
Total PET Bottle Capacity	240	300	360
# of Selections / Columns	6 / 8	12 / 10	12 / 10
Dimensions* - H x W x D	72" x 32.5" x 35"	72" x 39.5" x 35"	79" x 39.5" x 35"
Shipping Weight*	590 lbs.	660 lbs.	745 lbs.
Operation Voltage	115v 60Hz	115v 60Hz	115v 60Hz
Amp Rating	8	8	8
Energy Consumption (DOE)	≤ 3.8 kWh/day	≤ 3.9 kWh/day	≤ 4.3 kWh/day
Lighting	LED	LED	LED
Refrigerant	R-134a	R-134a	R-134a
Lock Type	E-Lock	E-Lock	E-Lock
Capacity per Column			
12oz. Can	68	68	80
20oz. PET Bottle**	30	30	36

* Dimensions and shipping weight will vary slightly.

** Product capacities will vary based on the shape and size of the bottle.



- The HVV is designed to attract attention in high volume locations. Standard Features include: LED lights, curved signface, molded DBV panel, large selection buttons, electronic locking system, ADA compliant, UL certified, ENERGY STAR qualified & meets or exceeds DOE & EPA requirements.
- The V21 has a full function MDB controller with DEX/UCS, recycler and wireless telemetry compatibility. The V21 and Vue control boards are completely interchangeable.
- Energy management features included on every model make the V21 one of the most energy efficient machines available: LED lighting, real time clock, lighting and refrigeration controls, cyclopentane injected foam insulation (HFC free) and now the option of **alternative natural refrigerant**.
- The V21 utilizes 24 volt, DC motors that are installed with only two screws for easy servicing. There are no micro switches or timing cams.
- The time tested V21 product delivery system design ensures reliable vending due to reduced sensitivity to package diameter and shape.
- Rugged top retainer ensures consistent product alignment every time the door is closed.
- The V21's epoxy coated vend chute provides smooth product delivery.
- The V21 stack allows for maximum flexibility during product loading. Most products can be loaded caps to back, butt-to-butt, or in combination.

SandenVendo America, Inc. offers a complete line of parts, accessories, supplies and add-on security devices - call or visit www.vendoco.com for more information.

PEPSI, PEPSI-COLA, and the PEPSI BIG BOLD BLUE design are registered trademarks of PepsiCo, Inc.



SandenVendo America, Inc.

10710 Sanden Drive, Dallas, TX 75238

P: 214-765-9066

F: 214-340-8029

P: 1-800-344-7216

F: 1-800-541-5684

www.vendoco.com



Copyright © 2015 SVA
Part # 1148988-04

REV F 4/15